
1	Unique identification code of the product type	PLIXXOPOL SF 640221 <i>Designation code: PU EN 14315-1 – CT4(20)-GT8(20)-TFT10(20)-FRC8(20)-MU5-CCC1</i>
2	Intended use/es	Thermal insulating products for buildings – Insitu formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products
3	Manufacturer	PLIXXENT BV Korte Groningerweg 1a 9607 PS Foxhol Nederland
4	Authorised representative	Not relevant
5	System/s of AVCP	System 3
6a	Harmonised standard	EN 14315-1:2013
	Notified body/ies	LGAI Technological Center, S.A. (APPLUS) Campus UAB Ronda de la Font del Carme, s/n E - 08193 Bellaterra (Barcelona) Spain Notified Body number : 0370 Instytut Techniki Budowlanej ul. Filtrowa 1 00-611 Warszawa Poland Notified Body number : 1488
6b	European Assessment Document European Technical Assessment Technical Assessment Body Notified body/ies	Not relevant

7 Declared performance/s **See table**

Essential characteristics	Performance	Specifications
Reaction to fire	E	EN 13501-1
Water permeability	NPD	EN 1609 Method B
Thermal resistance	See performance chart	EN 14315-1:2013
Water vapour permeability	5	EN 12086 method A
Compressive strength	NPD	EN 826:2013
Durability of reaction to fire against ageing/degradation	Reaction to fire does not decrease with time	EN 14315-1:2013
Durability of thermal resistance against ageing/degradation	See performance chart	EN 14315-1:2013
Durability of compressive strength against ageing/degradation	NPD	EN 14315-1:2013
Continuous glowing combustion	No harmonized test method available	EN 14315-1:2013

8 Appropriate Technical Documentation and/or Specific Technical Documentation **Not relevant**

Performance chart

Type of facing: None or diffusion open

Thickness	Declared aged thermal conductivity (λ_D)	Thermal resistance level (RD)
<i>mm</i>	<i>W/m·K</i>	<i>m²·K/W</i>
50	0,037	1,35
55	0,037	1,50
60	0,037	1,60
65	0,037	1,75
70	0,037	1,90
75	0,037	2,05
80	0,037	2,15
85	0,037	2,30
90	0,037	2,45
95	0,037	2,55
100	0,037	2,70
105	0,037	2,85
110	0,037	2,95
115	0,037	3,10
120	0,037	3,25
125	0,037	3,40
130	0,037	3,50
135	0,037	3,65
140	0,037	3,80
145	0,037	3,90
150	0,037	4,05
155	0,037	4,20
160	0,037	4,30
165	0,037	4,45
170	0,037	4,60
175	0,037	4,75
180	0,037	4,85
185	0,037	5,00
190	0,037	5,15
195	0,037	5,25
200	0,037	5,40
225	0,037	6,10
250	0,037	6,75
275	0,037	7,45
300	0,037	8,10

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name and function

Place and date of issue

Signature

Foxhol
18-12-2025

Foxhol
18-12-2025



R.H.C. Udo
Managing Director